



Hauteur A	Largeur B	Entraxe de raccordement C	Couleur	Capacité		Puissance du thermoplongeur recommandée			D	E	F	Volume [dm ³]	Poids [kg]
				75/65/20°C	90/70/20°C	MEG	REG	KTX					
[mm]	[mm]	[mm]		[W]		[W]			[mm]	[mm]	[mm]		
600	450	420	RAL 9003	282	353	300	300	300	420	420	90	1,6	5,0
	450	420	Silver Mat	282	353	300	300	300	420	420	90	1,6	5,0
	450	420	RAL 9005	282	353	300	300	300	420	420	90	1,6	5,0
	600	570	RAL 9003	361	451	400	400	400	570	420	90	1,9	6,3
	600	570	Silver Mat	361	451	400	400	400	570	420	90	1,9	6,3
	600	570	RAL 9005	361	451	400	400	400	570	420	90	1,9	6,3
780	450	420	RAL 9003	362	453	400	400	400	420	600	90	2,2	6,8
	450	420	Silver Mat	362	453	400	400	400	420	600	90	2,2	6,8
	450	420	RAL 9005	362	453	400	400	400	420	600	90	2,2	6,8
	600	570	RAL 9003	461	576	400	400	400	570	600	90	2,6	8,5
	600	570	Silver Mat	461	576	400	400	400	570	600	90	2,6	8,5
	600	570	RAL 9005	461	576	400	400	400	570	600	90	2,6	8,5
1185	450	420	RAL 9003	536	670	600	600	600	420	1005	90	3,4	10,4
	450	420	Silver Mat	536	670	600	600	600	420	1005	90	3,4	10,4
	450	420	RAL 9005	536	670	600	600	600	420	1005	90	3,4	10,4
	600	570	RAL 9003	689	861	800	800	800	570	1005	90	4,0	13,2
	600	570	Silver Mat	689	861	800	800	800	570	1005	90	4,0	13,2
	600	570	RAL 9005	689	861	800	800	800	570	1005	90	4,0	13,2
1680	450	420	RAL 9003	761	951	800	800	800	420	1500	90	4,8	15,0
	450	420	Silver Mat	761	951	800	800	800	420	1500	90	4,8	15,0
	450	420	RAL 9005	761	951	800	800	800	420	1500	90	4,8	15,0
	600	570	RAL 9003	957	1196	1000	1000	1000	570	1500	90	5,7	19,0
	600	570	Silver Mat	957	1196	1000	1000	1000	570	1500	90	5,7	19,0
	600	570	RAL 9005	957	1196	1000	1000	1000	570	1500	90	5,7	19,0